

Outdoor Lighting

Roadway LED



The Roadway LED is a green solution and great fit for streets, roads, long, narrow areas and parking lots. This energy-efficient luminaire delivers the light where it is needed while increasing visibility and reducing spill light to adjoining properties. Choose low to medium light output on wood or fiberglass poles (or mount on an existing pole). Available with one to four fixtures per pole, depending on the fixture/pole combination selected.

LED 50 | 75 | 105 | 150 | 215 | 280 watts
(Light Emitting Diode)

Mounting heights 25', 30', 35'

Color Gray, Black

Poles Fiberglass
Metal (*special conditions*)
Wood

Outdoor Lighting

Roadway LED

Light source: LED (*white*)

Lumens: 4,807 – 25,050 (*fixture dependent*)

Wattage	Light Pattern	IESNA Backlight-Uplight – Glare (BUG) Rating
LED 50	IESNA Type III (<i>medium oval</i>)	B1-U0-G1
LED 75	IESNA Type II (<i>long oval</i>)	B1-U0-G2
LED 105	IESNA Type II (<i>long oval</i>)	B2-U0-G3
LED 150	IESNA Type III (<i>medium oval</i>)	B2-U0-G2
LED 215	IESNA Type III (<i>medium oval</i>)	B3-U0-G3
LED 280	IESNA Type III (<i>medium oval</i>)	B3-U0-G4



Color temperature: 4,000K

Warm-up and restrike time: Instant on (*no warm-up or restrike time*)

Poles available:

Name	Mounting height	Color
Fiberglass	25', 30', 35'	Gray
Fiberglass	25', 30', 35'	Black (<i>additional cost</i>)
Wood	25', 30', 35'	Standard
Metal (<i>special conditions</i>)*	25', 30', 35'	Gray

Features

Little or no installation cost

Design services by lighting professionals included

Maintenance included

Electricity included

Warranty included

One low monthly cost on your electric bill

Turnkey operation

Backed by over 40 years of experience

Benefits

Frees up capital for other projects

Meets industry standards and lighting ordinances

Eliminates high and unexpected repair bills

Less expensive than metered service

Worry-free

Convenience and savings for you

Provides hassle-free installation and service

A name you can trust today ... and tomorrow

*2' raised foundation available when required.