

FIBERGLASS ENCLOSURE AERATION BLOWER PACKAGES

Aquapoint positive displacement blower systems housed in fiberglass enclosures provide exceptional weather protection and sound attenuation. The durable, light weight and easy to install fiberglass enclosures are non-conductive and non-corrosive ensuring safe, long lasting blower operation. The gel coat exterior is designed to resist ultraviolet degradation and will never crack, peel or require painting. A stainless steel support arm and locking hood allow for easy maintenance access. Choose from a variety of optional features to reduce noise, monitor component conditions and ensure efficient operation. Contact AquaPoint for application specific blower sizing and specifications.



STANDARD BLOWER PACKAGES

MODEL	BASE	BLOWER MODEL	MOTOR HP	DISCHARGE
APFB-1.5	FE01	URAI-22	1.5	1"
APFB-2	FE01	URAI-24	2	2"
APFB-3	FE01	URAI-24	3	2"
APFB-5	FE01	URAI-33	5	2"
APFB-7.5	FE01	URAI-36	7.5	2.5"
APFB-10	FE02	URAI-45	10	2.5"
APFB-15	FE02	URAI-47	15	3"

STANDARD FEATURES

- Weather Proof Fiberglass Enclosure
- Roots URAI Dual-Lobe Blower Blocks
- Premium Efficient ODP Motors
- Adjustable Motor Base
- Intake Filter / Silencer
- Dual V-Belt Drive System
- Check Valve
- Pressure Relief Valve
- Galvanized Steel Discharge Piping
- Flexible Discharge Connection
- Pressure Gauge
- Louvered Vent
- Ventilation Fan

OPTIONAL FEATURES

- **Kaeser Tri-Lobe Blower Blocks for Sound Reduction**
- Premium Efficient TEFC Motors
- Discharge Silencer (Field Installed)
- Temperature Gauge
- Filter Gauge
- Pressure Shut Off Switch
- Foam Insulation
- Heating Elements
- Additional Louvered Vents
- Stainless Steel Discharge Piping
- Integral VFD Controls

39 Tarkiln Place
 New Bedford, MA 02745
 T (508) 985-9050 | F (508) 985-9072

AQUAPOINT.COM