

ANNEXATION AREA

Commencing at a beginning point at railroad spike in center of rail road right of way with a bearing S 33-41'42" W a distance 1711.89 to a point;
Thence bearing S 30-02-39 E a distance of 511.99 to a point;
Thence bearing S 22-02-57 E a distance of 214.14 to a point;
Thence bearing N 89-54-26 E a distance of 632.05 to a point;
Thence bearing N 32-43-44 E a distance of 764.69 to a point;
Thence bearing S 54-25-26 E a distance of 34.32 to a point;
Thence bearing S 55-09-12 E a distance of 380.94 to a point;
Thence bearing S 55-09-35 E a distance of 206.48 to a point;
Thence bearing S 55-04-30 E a distance of 195.40 to a point;
Thence bearing S 55-08-45 E a distance of 234.38 to a point;
Thence bearing S 55-07-34 E a distance of 359.24 to a point;
Thence bearing S 55-18-55 E a distance of 345.47 to a point;
Thence bearing S 14-42-23 E a distance of 568.88 to a point;
Thence bearing S 14-46-34 E a distance of 29.19 to a point;
Thence bearing S 77-01-11 W a distance of 74.42 to a point;
Thence bearing S 78-23-49 W a distance of 81.75 to a point;
Thence bearing S 79-33-50 W a distance of 77.49 to a point;
Thence bearing S 82-42-48 W a distance of 73.03 to a point;
Thence bearing S 85-13-23 W a distance of 55.53 to a point;
Thence bearing S 84-48-16 W a distance of 78.50 to a point;
Thence bearing S 85-40-48 W a distance of 584.75 to a point;
Thence bearing S 87-22-38 W a distance of 103.55 to a point;
Thence bearing S 89-45-47 W a distance of 86.38 to a point;
Thence bearing N 86-25-15 W a distance of 103.20 to a point;
Thence bearing N 85-15-41 W a distance of 60.38 to a point;
Thence bearing N 86-31-38 W a distance of 79.13 to a point;
Thence bearing S 89-43-50 W a distance of 70.04 to a point;
Thence bearing S 86-54-24 W a distance of 73.86 to a point;
Thence bearing S 85-03-36 W a distance of 110.24 to a point;
Thence bearing S 84-20-08 W a distance of 203.53 to a point;
Thence bearing S 85-42-25 W a distance of 68.90 to a point;
Thence bearing S 87-55-29 W a distance of 146.22 to a point;
Thence bearing S 89-59-37 W a distance of 183.93 to a point;
Thence bearing S 87-35-01 W a distance of 76.59 to a point;
Thence bearing S 83-41-29 W a distance of 76.36 to a point;
Thence bearing S 77-47-15 W a distance of 54.20 to a point;
Thence bearing S 72-12-38 W a distance of 77.46 to a point;
Thence bearing S 70-21-24 W a distance of 58.68 to a point;
Thence bearing N 00-58-46 E a distance of 144.23 to a point;

Thence bearing N 88-21-29 W a distance of 1460.97 to a point;
Thence bearing N 88-23-18 W a distance of 224.82 to a point;
Thence bearing N 88-19-24 W a distance of 998.37 to a point;
Thence bearing N 88-22-07 W a distance of 413.69 to a point;
Thence bearing S 21-17-48 E a distance of 1349.99 to a point;
Thence bearing S 20-58-51 E a distance of 29.30 to a point;
Thence bearing S 52-27-37 W a distance of 1080.00 to a point;
Thence bearing S 80-25-44 W a distance of 632.57 to a point;
Thence bearing N 20-53-22 E a distance of 98.92 to a point;
Thence bearing N 07-37-53 W a distance of 130.85 to a point;
Thence bearing N 22-41-18 W a distance of 156.00 to a point;
Thence bearing N 38-08-19 W a distance of 57.54 to a point;
Thence bearing N 53-49-39 W a distance of 54.75 to a point;
Thence bearing N 31-41-26 W a distance of 66.36 to a point;
Thence bearing N 09-54-31 W a distance of 62.48 to a point;
Thence bearing N 22-11-02 E a distance of 45.81 to a point;
Thence bearing N 05-34-16 W a distance of 57.29 to a point;
Thence bearing N 34-04-07 W a distance of 59.15 to a point;
Thence bearing N 38-27-52 W a distance of 67.95 to a point;
Thence bearing S 88-42-40 W a distance of 32.59 to a point;
Thence bearing N 05-06-16 W a distance of 88.13 to a point;
Thence bearing N 51-58-50 E a distance of 88.37 to a point;
Thence bearing N 27-32-06 W a distance of 84.23 to a point;
Thence bearing N 00-30-47 E a distance of 110.54 to a point;
Thence bearing N 79-10-42 W a distance of 128.05 to a point;
Thence bearing S 22-29-51 W a distance of 41.23 to a point;
Thence bearing N 76-53-59 W a distance of 135.27 to a point;
Thence bearing N 11-24-37 E a distance of 75.68 to a point;
Thence bearing N 05-49-48 W a distance of 53.31 to a point;
Thence bearing N 43-16-17 E a distance of 130.27 to a point;
Thence bearing N 54-34-54 E a distance of 175.62 to a point;
Thence bearing N 12-15-42 W a distance of 133.64 to a point;
Thence bearing N 82-11-25 W a distance of 61.51 to a point;
Thence bearing N 19-27-56 W a distance of 92.18 to a point;
Thence bearing N 01-43-15 W a distance of 237.06 to a point;
Thence bearing N 70-17-33 W a distance of 173.78 to a point;
Thence bearing N 21-43-33 W a distance of 105.36 to a point;
Thence bearing N 74-50-03 W a distance of 45.74 to a point;
Thence bearing N 21-46-07 W a distance of 180.77 to a point;
Thence bearing N 67-10-12 E a distance of 81.96 to a point;
Thence bearing N 14-19-55 W a distance of 158.46 to a point;
Thence bearing N 79-19-25 W a distance of 87.16 to a point;
Thence bearing N 21-44-03 E a distance of 103.83 to a point;
Thence bearing N 07-49-07 W a distance of 177.57 to a point;

Thence bearing S 76-49-55 W a distance of 43.26 to a point;
Thence bearing N 59-26-58 W a distance of 73.53 to a point;
Thence bearing N 03-39-56 W a distance of 138.00 to a point;
Thence bearing N 40-22-54 E a distance of 120.00 to a point;
Thence bearing N 63-08-02 W a distance of 140.54 to a point;
Thence bearing N 05-57-03 W a distance of 205.69 to a point;
Thence bearing N 88-18-48 W a distance of 82.00 to a point;
Thence bearing N 44-24-01 W a distance of 228.73 to a point;
Thence bearing N 49-44-06 E a distance of 148.63 to a point;
Thence bearing N 11-58-03 W a distance of 301.04 to a point;
Thence bearing N 42-34-00 E a distance of 133.39 to a point;
Thence bearing N 06-56-07 E a distance of 302.90 to a point;
Thence bearing N 17-47-25 W a distance of 399.06 to a point;
Thence bearing N 07-58-06 W a distance of 149.98 to a point;
Thence bearing N 76-16-16 W a distance of 247.21 to a point;
Thence bearing N 26-43-40 W a distance of 180.87 to a point;
Thence bearing N 13-12-57 E a distance of 161.25 to a point;
Thence bearing N 10-54-55 W a distance of 198.22 to a point;
Thence bearing S 88-20-07 E a distance of 633.89 to a point;
Thence bearing N 01-43-46 E a distance of 843.40 to a point;
Thence bearing N 88-20-15 W a distance of 216.42 to a point;
Thence bearing N 02-42-31 E a distance of 647.47 to a point;
Thence bearing S 86-25-11 E a distance of 486.15 to a point;
Thence bearing S 86-22-56 E a distance of 717.74 to a point;
Thence bearing S 01-16-33 W a distance of 503.48 to a point;
Thence bearing S 89-00-00 E a distance of 2653.46 to a point;
Thence bearing S 89-00-00 E a distance of 90.19 to a point;
Thence bearing S 44-27-31 E a distance of 450.20 to a point;
Thence bearing S 46-02-32 E a distance of 76.57 to a point;
Thence bearing S 47-16-35 E a distance of 69.72 to a point;
Thence bearing S 48-35-29 E a distance of 74.10 to a point;
Thence bearing S 50-26-38 E a distance of 72.91 to a point;
Thence bearing S 51-33-51 E a distance of 75.43 to a point;
Thence bearing S 53-32-20 E a distance of 71.53 to a point;
Thence bearing S 54-36-02 E a distance of 74.59 to a point;
Thence bearing S 56-14-56 E a distance of 77.12 to a point;
Thence bearing S 57-57-21 E a distance of 75.15 to a point;
Thence bearing S 59-15-37 E a distance of 75.94 to a point;
Thence bearing S 60-50-49 E a distance of 76.33 to a point;
Thence bearing S 62-11-18 E a distance of 75.58 to a point;
Thence bearing S 64-40-16 E a distance of 147.70 to a point;
Thence bearing S 66-49-52 E a distance of 73.82 to a point;
Thence bearing S 68-14-53 E a distance of 76.14 to a point;
Thence bearing S 70-03-36 E a distance of 109.11 to a point;

Thence bearing N 04-39-33 E a distance of 51.72 to a point;
Thence bearing N 04-39-33 E a distance of 560.07 to a point;
Thence bearing N 04-40-11 E a distance of 44.81 to a point;
Thence bearing N 04-40-11 E a distance of 80.93 to a point;
Thence bearing N 04-40-11 E a distance of 178.79 to a point;
Thence bearing S 51-45-49 E a distance of 338.62 to a point;
Thence curve length 323.30 with a radius 3812.1 at a chord bearing S 50-06-26 E with a chord distance of 323.20 to a point;
Thence bearing S 44-45-04 W a distance of 111.74 to a point;
Thence bearing S 44-45-04 W a distance of 28.25 to a point;
Thence bearing S 49-44-31 E a distance of 73.26 to a point;
Thence bearing S 27-23-29 W a distance of 298.56 to a point;
Thence bearing S 23-22-48 W a distance of 203.89 to the beginning point;

Said described parcel contains 628.04 acres, more or less, subject to any and all easements, reservations, restrictions and conveyances of record.